



2 year warranty

Quality Compressed Air Products

Contractor Series

DD-1004







DD-1503



Direct Drive Units have splash lubricated pump with cast iron sleeve for longer life

- Belt Drive Units have durable cast iron pumps
- Splash type lubrication
- Steel valves for longer life
- All electrical units draw 15 amps or under
- Manual reset for overload protection
- Dual control-start/stop with pressure switch or constant speed operation for PUK-1508MDC
- PUK-6508G equipped with Honda Gas Engine
- Idle-down throttle control for gas belt drive unit
- All units are factory tested prior to shipment
- For Farms and professional contractors











Specifications





| MODEL | | RUNNING H | - | FM | MAX. | VOLTAGE/ | AMP DRAW | TANK | PUMP | WEIGHT | |
|-------------|-------|-----------|--------|--------|------|------------|-----------|------|------|--------|---------------------|
| MODEL | HP | @ 40 PSI | 40 P31 | 90 PSI | PSI | PHASE | @ 125 PSI | SIZE | RPM | LBS | REMARKS |
| DD-1004 | 1 | 1 | 4.5 | 4.0 | 125 | 115V/1PH | 15 | 4 | 1720 | 65 | PANCAKE BOTTOM |
| ND-1003 | 1 | 1 | 4.5 | 4.0 | 125 | 115V/1PH | 13 | 3.2 | 3450 | 70 | HOT DOG |
| ND-1008 | 1 | 1 | 4.5 | 4.0 | 125 | 115V/1PH | 13 | 6.6 | 3450 | 70 | PORTABLE |
| DD-1503 | 1.5 | 1.5 | 6.0 | 4.6 | 125 | 115V/1PH | 14 | 3.2 | 1720 | 55 | HOT DOG |
| DD-2022B | 2 | 1.5 | 6.0 | 4.6 | 125 | 115V/1PH | 15 | 4 | 1720 | 80 | TWIN TANK BOTTOM |
| DP-2022W | 2 | 1.5 | 6.0 | 4.6 | 125 | 115V/1PH | 15 | 4 | 3450 | 84 | TWIN STACK PORTABLE |
| DP-3008 | 3 | 2 | 7.3 | 6.0 | 125 | 115V/1PH | 15 | 6.6 | 3450 | 73 | PORTABLE |
| PUK-1508MD0 | C 1.5 | 1.5 | 6.6 | 6.0 | 125 | 115V/1PH | 15 | 8 | 1100 | 214 | WHEELBARROW |
| PUK-6508G | 5.5 | 5.5 | 16.5 | 14.0 | 125 | 5.5 HP GAS | S N/A | 8 | 900 | 250 | WHEELBARROW |





Quality Compressed Air Products

OIL FREE

Contractor Series



LA-5702





- Die cast aluminum pump with cast iron sleeve
- Steel valves for longer life
- Oilless means maintenance free
- All electrical units draw 15 amps or under
- Manual reset for overload protection
- All units are factory tested prior to shipment
- For Farms, professional contractors, home & hobbyists







Specifications

DMEGA

| MODEL | PEAK HP | RUNNING H @ 40 PSI | _ | FM 90 PSI | MAX. PSI | VOLTAGE/ PHASE | AMP DRAW @ 125 PSI | TANK SIZE | PUMP RPM | WEIGHT LBS | REMARKS |
|----------|------------|-----------------------|-----|--------------|-------------|-------------------|-----------------------|--------------|-------------|---------------|----------------|
| MB-2000G | .5 | .5 | 1.4 | .90 | 125 | 115V/1PH | 5 | N/A | 1720 | 10 | NO TANK |
| PN-1004L | 1 | .5 | 1.4 | .90 | 125 | 115V/1PH | 5 | 1 | 1720 | 17 | SIDE TANK |
| LA-5702 | 1.5 | .75 | 3.0 | 2.3 | 125 | 115V/1PH | 8 | 2 | 1720 | 35 | HOT DOG |
| LA-5708 | 1.5 | .75 | 3.0 | 2.3 | 125 | 115V/1PH | 8 | 6.6 | 1720 | 55 | PORTABLE |
| LA-5721 | 1.5 | .75 | 3.0 | 2.3 | 125 | 115V/1PH | 8 | 2 | 1720 | 40 | TWIN STACK |
| MA-9004 | 1.5 | 1.5 | 5.8 | 4.4 | 125 | 115V/1PH | 15 | 4 | 1720 | 63 | PANCAKE-BOTTOM |